

STUCOFIX



Ready to use acrylic putty



■ PROPERTIES

Water soluble white putty, based on acrylic styrene resins. It applies easily and smoothly. Dries quickly and sands easily without bursting creating a smooth and durable surface without defects.

■ ADVANTAGES

- Ready for use.
- Exceptional adhesion to concrete, plaster and wood.
- Great filling ability.
- Resistant to moisture and frost..

■ APPLICATIONS

STUCOFIX smooths out all surfaces made of gypsum and marble-based plaster, gypsum boards. It is also suitable for wood surfaces like doors, windows and even wood boats. It perfectly seals all nail holes on various surfaces.

■ USE

1. Surface preparation

Surfaces must be clean, dry and free from loose sections and oils. They also have to be dry for at least

30 days from their construction (for marble-based plaster or concrete surfaces).

2. Application

Apply the product as is, using a putty knife or an airless spray gun. Apply one to two coats, 0.5mm thick each one. Apply the second coat once the first one is dry. Allow for 2-3 hours to pass and sand the surface using the appropriate sandpaper. The surface can be repainted with emulsion, acrylic paints or enamel paint.

■ CLEANING

Clean all tools with water, immediately after use.

■ CONSUMPTION

1kg/2-3m², depending on the surface.

■ STORAGE

Store in the factory sealed packaging, in places protected from frost, for 18 months from date of production.



Ready to use acrylic putty

■ SAFETY DIRECTIONS

The product needs no hazard labeling under current European and National legislation.

However, it is recommended to keep away from the reach of -children. If swallowed, seek immediate medical advice and show the container or label.

■ PACKAGING

Carton box with 24pcs of 200gr each one

Carton box with 18pcs of 400gr each one

Carton box with 24pcs of 800gr each one

5kg, 20kg containers

TECHNICAL SPECIFICATIONS	
■ Form - Color	Putty - White
■ Density	1.70±0.08kg/l
■ Application temperature	From +8°C to +35°C
■ Painting/Wallpaper installation	After 24 hours

DUROSTICK S.A.,

MANUFACTURING OF ADHESIVES,

PAINTS & MORTARS

ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00,

Tel: +30 211 60 03 500-599, +30 210 55 16 500,

+30 210 55 98 350, Fax: +30 210 55 99 612

THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44,

STREET, DA 10, GR: 570 22,

Tel: +30 2310 795 797, +30 2310 797 365,

Fax: +30 2310 797 367

Email: info@durostick.com